



SAFETY DATA SHEET 2 PK EPOXY FINISH BASE

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010, According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name 2 PK EPOXY FINISH BASE

Product number 0079 - Non Lead (incl. 579 & 6579 Lines Dacmix)

Internal identification Also including 6579 (L/F) and 8579 Line Dacmix Reduced Gloss Levels.

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Paint.

1.3. Details of the supplier of the safety data sheet

Supplier Dacrylate Paints Ltd,
Lime Street,
Kirkby-in-Ashfield
Nottingham NG17 8AL
Tel: +44 (0) 1623-753845
Fax: +44 (0) 1623-757151

Contact person sales@dacrylate.co.uk

1.4. Emergency telephone number

National emergency telephone number +44 (0) 1623 753845 08:30-17:00 MON-FRI

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification

Physical hazards Flam. Liq. 3 - H226

Health hazards Skin Irrit. 2 - H315 Eye Dam. 1 - H318 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 3 - H412

Classification (67/548/EEC or 1999/45/EC) Xn;R20. Xi;R36/38. R43. N;R51/53. R10.

Human health Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.

Environmental This product may cause harm to the environment. See Section 12 Ecological Information.

Physicochemical See Section 7.2 Storage Class. See Section 5.2 Hazardous combustion products. See Section 10: Stability and reactivity

2.2. Label elements

2 PK EPOXY FINISH BASE

Pictogram



Signal word

Danger

Hazard statements

H226 Flammable liquid and vapour.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H318 Causes serious eye damage.
 H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P261 Avoid breathing vapour/spray.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.
 P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
 P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish.
 P403+P235 Store in a well-ventilated place. Keep cool.
 P501 Dispose of contents/container in accordance with national regulations.

Supplemental label information

EUH205 Contains epoxy constituents. May produce an allergic reaction.

Contains

XYLENE, EPOXY RESIN (Number average MW <= 700), 1,2,4-TRIMETHYLBENZENE, MESITYLENE, ISO-BUTANOL

Supplementary precautionary statements

P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P241 Use explosion-proof electrical equipment.
 P242 Use only non-sparking tools.
 P243 Take precautionary measures against static discharge.
 P264 Wash contaminated skin thoroughly after handling.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTER/doctor.
 P321 Specific treatment (see medical advice on this label).
 P332+P313 If skin irritation occurs: Get medical advice/attention.
 P362+P364 Take off contaminated clothing and wash it before reuse.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

2 PK EPOXY FINISH BASE

EPOXY RESIN (Number average MW <= 700)	10-30%
CAS number: 25068-38-6	EC number: 500-033-5
Classification Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) R43 Xi;R36/38 N;R51/53
XYLENE	10-30%
CAS number: 1330-20-7	EC number: 215-535-7
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H312 Acute Tox. 4 - H332 Skin Irrit. 2 - H315	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20/21 Xi;R38
ISO-BUTANOL	5-10%
CAS number: 78-83-1	EC number: 201-148-0
Classification Flam. Liq. 3 - H226 Skin Irrit. 2 - H315 Eye Dam. 1 - H318 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) R10 Xi;R37/38,R41 R67
SOLVENT NAPHTHA, PETROLEUM; LIGHT AROMATIC	5-10%
CAS number: 64742-88-7	
Classification Flam. Liq. 3 - H226 Muta. 1A - H340 Carc. 1A - H350 Asp. Tox. 1 - H304	Classification (67/548/EEC or 1999/45/EC) Xn;R65. Xi;R37. N;R51/53. R10.
1,2,4-TRIMETHYLBENZENE	1-5%
CAS number: 95-63-6	EC number: 202-436-9
Classification Flam. Liq. 3 - H226 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) R10 Xn;R20 Xi;R36/37/38 N;R51/53

2 PK EPOXY FINISH BASE

MESITYLENE		1-5%
CAS number: 108-67-8		EC number: 203-604-4
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xi;R37 N;R51/53	
STOT SE 3 - H335		
Aquatic Chronic 2 - H411		
BUTANOL-norm		<1%
CAS number: 71-36-3		EC number: 200-751-6
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R22 Xi;R37/38,R41 R67	
Acute Tox. 4 - H302		
Skin Irrit. 2 - H315		
Eye Dam. 1 - H318		
STOT SE 3 - H336		
CUMENE		<1%
CAS number: 98-82-8		EC number: 202-704-5
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 Xn;R65 Xi;R37 N;R51/53	
Acute Tox. 4 - H302		
STOT SE 3 - H335		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		
2-METHOXY-1-METHYLETHYL ACETATE		<1%
CAS number: 108-65-6		EC number: 203-603-9
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10	
BUTYL ACETATE -norm		
CAS number: 123-86-4		EC number: 204-658-1
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	R10 R66 R67	
STOT SE 3 - H336		

2 PK EPOXY FINISH BASE

ETHYLBENZENE	<1%
CAS number: 100-41-4	EC number: 202-849-4
Classification Flam. Liq. 2 - H225 Acute Tox. 4 - H332 Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 STOT SE 3 - H335 STOT RE 2 - H373 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) F;R11 Xn;R20
DI-ISOBUTYL KETONE	<1%
CAS number: 108-83-8	EC number: 203-620-1
Classification Flam. Liq. 3 - H226 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) R10 Xi;R37
WHITE SPIRIT	<1%
CAS number: 64742-88-7	EC number: 265-191-7
Classification Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	Classification (67/548/EEC or 1999/45/EC) Xn;R65. N;R51/53. R10.
FORMALDEHYDE ...%	<1%
CAS number: 50-00-0	EC number: 200-001-8
Classification Acute Tox. 3 - H301 Acute Tox. 3 - H311 Acute Tox. 3 - H331 Skin Corr. 1B - H314 Skin Sens. 1 - H317 Carc. 2 - H351 STOT SE 3 - H335	Classification (67/548/EEC or 1999/45/EC) Carc. Cat. 3;R40 T;R23/24/25 C;R34 R43

The Full Text for all R-Phrases and Hazard Statements are Displayed in Section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

The severity of the symptoms described will vary depending on the concentration and the length of exposure. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.

2 PK EPOXY FINISH BASE

Inhalation	Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this Safety Data Sheet to the medical personnel.
Ingestion	Remove affected person from source of contamination. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing. Use barrier creams to prevent skin contact. Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. In case of insufficient ventilation, wear suitable respiratory equipment.

4.2. Most important symptoms and effects, both acute and delayed

General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Harmful if inhaled Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Harmful if swallowed. May cause nausea, stomach pain and vomiting.
Skin contact	Skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	May cause severe eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor	No specific recommendation given, but first aid may still be required in case of accidental exposure, inhalation or ingestion of this chemical. If in doubt, GET MEDICAL ATTENTION PROMPTLY! In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
-----------------------------	--

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Specific hazards	Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. If a fire or if heated, a pressure increase will occur and the container may burst with the risk of subsequent explosion. The product is flammable.
Hazardous combustion products	In case of fire, toxic gases (CO, CO ₂ , NO _x) may be formed. Acrid smoke or fumes. Other pyrolysis products typical of burning an organic material. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m ³ . In the event of a fire and/or explosion, do not breathe fumes.

5.3. Advice for firefighters

2 PK EPOXY FINISH BASE

Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken without appropriate training or involving any personal risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions	Do not handle broken packages without protective equipment. If ventilation is inadequate, suitable respiratory protection must be worn. Take care as floors and other surfaces may become slippery. Wash thoroughly after dealing with a spillage. Where anti slip aggregates, powders or similar are added/post added to a paint, the potential for the generation of respirable dust during handling and use can occur. In such cases, occupational exposures to respirable dust should be monitored and controlled. In the case of exposure to prolonged or high levels of air borne dust, wear a personal respirator in compliance with national legislation. No smoking, sparks, flames or other sources of ignition near spillage.
For non-emergency personnel	Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear suitable respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable materials. See also the information in "For non-emergency personnel".

6.2. Environmental precautions

Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
----------------------------------	--

6.3. Methods and material for containment and cleaning up

Methods for cleaning up	No smoking, sparks, flames or other sources of ignition near spillage. Collect and place in suitable waste disposal containers and seal securely. If involved in a fire, shut off flow if it can be done without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. Ensure that waste and contaminated materials are collected and removed from the work area as soon as possible in a suitably labelled container. The accumulation of contaminated rags and application cloths may result in spontaneous combustion. This is particularly important in the case of products containing a high level of drying oils such as teak oil, linseed oil etc. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.
--------------------------------	---

6.4. Reference to other sections

Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see section 13.
------------------------------------	---

SECTION 7: Handling and storage

7.1. Precautions for safe handling

2 PK EPOXY FINISH BASE

Usage precautions	Avoid contact with skin and eyes. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. All handling should only take place in well-ventilated areas. Static electricity and formation of sparks must be prevented. Dust may form explosive mixture with air. Take precautionary measures against static discharges. Storage tanks and other containers must be earthed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Paints based on pitch, coal tar, high temp (CAS 65996-93-2) may cause sensitivity to sunlight. To reduce sun sensitivity, a sun blocking lotion (SPE 15+) can also be applied prior to application of a protective cream.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions	Keep away from food, drink and animal feeding stuffs. Keep away from oxidising materials, heat and flames. Paints containing aluminium must not get in contact with water during storage. Exercise caution when opening to allow pressure release. Keep container tightly closed and in a well-ventilated place. Avoid/separate from strong acids, alkalis, oxidising and reducing agents. Observe the label precautions. Store at temperatures between 5°C and 35°C (32 to 95°F).
----------------------------	--

Storage class	Flammable liquid storage.
----------------------	---------------------------

7.3. Specific end use(s)

Specific end use(s)	The identified uses for this product are detailed in Section 1.2. Restricted to professional users.
----------------------------	---

SECTION 8: Exposure Controls/personal protection

8.1. Control parameters

Occupational exposure limits

XYLENE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 220 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 441 mg/m³(Sk)

ISO-BUTANOL

Long-term exposure limit (8-hour TWA): WEL 50 ppm 154 mg/m³

Short-term exposure limit (15-minute): WEL 75 ppm 231 mg/m³

BUTANOL-norm

Long-term exposure limit (8-hour TWA): WEL

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 154 mg/m³(Sk)

CUMENE

Long-term exposure limit (8-hour TWA): WEL 25 ppm(Sk) 125 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 50 ppm(Sk) 250 mg/m³(Sk)

2-METHOXY-1-METHYLETHYL ACETATE

Long-term exposure limit (8-hour TWA): WEL 50 ppm(Sk) 274 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 100 ppm(Sk) 548 mg/m³(Sk)

BUTYL ACETATE -norm

Long-term exposure limit (8-hour TWA): WEL 150 ppm 724 mg/m³

Short-term exposure limit (15-minute): WEL 200 ppm 966 mg/m³

ETHYLBENZENE

Long-term exposure limit (8-hour TWA): WEL 100 ppm(Sk) 441 mg/m³(Sk)

Short-term exposure limit (15-minute): WEL 125 ppm(Sk) 552 mg/m³(Sk)

2 PK EPOXY FINISH BASE

DI-ISOBUTYL KETONE

Long-term exposure limit (8-hour TWA): WEL 25 ppm 148 mg/m³

Short-term exposure limit (15-minute): WEL

WHITE SPIRIT

Long-term exposure limit (8-hour TWA): WEL 350 mg/m³(Sk)

FORMALDEHYDE ...%

Long-term exposure limit (8-hour TWA): WEL 2 ppm 2.5 mg/m³

Short-term exposure limit (15-minute): WEL 2 ppm 2.5 mg/m³

WEL = Workplace Exposure Limit

Ingredient comments WEL = Workplace Exposure Limits

XYLENE (CAS: 1330-20-7)

DNEL

- Inhalation; Short term : 442 mg/m³

8.2. Exposure controls

Protective equipment



Note: When spraying, the use of a suitable/approved respirator is advised.

Appropriate engineering controls No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.

Personal protection Advice on personal protection is applicable for high exposure levels. Select proper personal protection based on a risk assessment of the actual exposure scenario.

Eye/face protection The following protection should be worn: Chemical splash goggles. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.

Hand protection Wear protective gloves made of the following material: Polyvinyl alcohol (PVA). Viton rubber (fluoro rubber).

Other skin and body protection Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact.

Hygiene measures Wash hands at the end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes contaminated. Use appropriate skin cream to prevent drying of skin. When using do not eat, drink or smoke. Do not smoke in work area.

Respiratory protection No specific recommendations. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.

Environmental exposure controls Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

Colour Various colours.

2 PK EPOXY FINISH BASE

Odour	Characteristic/of solvents
Odour threshold	Not determined.
pH	Not relevant.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	23°C
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 10.5%
Other flammability	Not known.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	~ 1.40 - 1.60 @ @ 20°C
Bulk density	Not determined.
Solubility(ies)	Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	May form explosive mixtures with air.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.
Comments	Information given is applicable to the product as supplied.

9.2. Other information

Other information Soluble in most organic solvents.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity The following materials may react with the product: Acids. Alkalis. Oxidising materials.

10.2. Chemical stability

Stability Stable at normal ambient temperatures and when used as recommended. Further information on correct storage: refer to Section 7.

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions None under normal processing Vapours may form explosive mixtures with air.

2 PK EPOXY FINISH BASE

10.4. Conditions to avoid

Conditions to avoid Avoid heat, flames and other sources of ignition. Avoid contact with strong oxidising agents. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to conditions to heat or sources of ignition. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m³. Avoid extremes of temperature and direct sunlight.

10.5. Incompatible materials

Materials to avoid Strong oxidising agents.

10.6. Hazardous decomposition products

Hazardous decomposition products Thermal decomposition or combustion products may include the following substances: Carbon monoxide (CO). Carbon dioxide (CO₂). Oxides of nitrogen. Acrid smoke or fumes. In case of fire and/or explosion, do not breathe fumes.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological effects Based on the properties of the epoxy constituents and considering toxicological data on similar preparations, this preparation may be a skin sensitiser and an irritant. It contains low molecular epoxy constituents which are irritating to eyes, mucous membrane and skin. Repeated skin contact may lead to irritation and to sensitisation, possibly with cross-sensitisation to other epoxies. Skin contact with the preparation and exposure to spray mist and vapour should be avoided.

Acute toxicity - oral

ATE oral (mg/kg) 5,790.57905791

Acute toxicity - dermal

ATE dermal (mg/kg) 8,695.65217391

Acute toxicity - inhalation

ATE inhalation (vapours mg/l) 86.95652174

General information

This product is unlikely to harm health, given normal and proper handling and hygienic precautions. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Harmful by inhalation. Irritating to respiratory system.

Ingestion

Irritating. May cause nausea, stomach pain and vomiting.

Skin contact

Harmful in contact with skin. Irritating to skin.

Eye contact

Harmful in contact with eyes. Irritating to eyes.

Acute and chronic health hazards

The product contains an epoxy resin. May cause sensitisation or allergic reactions in sensitive individuals.

Route of entry

Inhalation Ingestion. Skin and/or eye contact Oral

Additional Information:

For further information, please refer to Sections 4 and 8 respectively..

Toxicological information on ingredients.

XYLENE

2 PK EPOXY FINISH BASE

Toxicological effects	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. High vapour concentrations can cause headaches, dizziness and nausea.
<u>Acute toxicity - oral</u>	
Acute toxicity oral (LD₅₀ mg/kg)	4,300.0
Species	Rat
<u>Acute toxicity - dermal</u>	
Acute toxicity dermal (LD₅₀ mg/kg)	2,000.0
Species	Rabbit
ATE dermal (mg/kg)	2,000.0
<u>Acute toxicity - inhalation</u>	
Acute toxicity inhalation (LC₅₀ vapours mg/l)	11.0
Species	Rat
ATE inhalation (vapours mg/l)	11.0
<u>Skin corrosion/irritation</u>	
Animal data	No information available.
Human skin model test	Irritating.
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes eye irritation
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	There is no evidence that the product can cause respiratory hypersensitivity.
<u>Skin sensitisation</u>	
Skin sensitisation	No information available.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
<u>Carcinogenicity</u>	
Carcinogenicity	No evidence of carcinogenicity
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	This substance has no evidence of toxicity to reproduction.
Reproductive toxicity - development	No information available.

2 PK EPOXY FINISH BASE

Specific target organ toxicity - single exposure

STOT - single exposure Central and/or peripheral nervous system damage.

Target organs Central nervous system Liver Kidneys

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No information available.

Aspiration hazard

Aspiration hazard Aspiration hazard if swallowed.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Harmful by inhalation.

Ingestion Irritating. May cause nausea, stomach pain and vomiting.

Skin contact Harmful in contact with skin. Irritating to skin.

Eye contact The product is irritating to eyes and skin.

Route of entry Oral Skin and/or eye contact Inhalation Ingestion

Target organs Central nervous system

Medical symptoms Allergies. Irritation of eyes and mucous membranes. Headache. Fatigue. Dizziness.

SOLVENT NAPHTHA, PETROLEUM; LIGHT AROMATIC

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 5,051.0

Species Rat

ATE oral (mg/kg) 5,051.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 4,001.0

Species Rabbit

ATE dermal (mg/kg) 4,001.0

Serious eye damage/irritation

Serious eye damage/irritation Not Irritating

Respiratory sensitisation

Respiratory sensitisation There is no evidence that the product can cause respiratory hypersensitivity.

Skin sensitisation

Skin sensitisation Not expected to be a skin sensitizer

2 PK EPOXY FINISH BASE

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity No evidence of carcinogenicity

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development No evidence of development toxicity

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

Aspiration hazard

Aspiration hazard No information available.

General information Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

Ingestion Irritating. May cause nausea, stomach pain and vomiting.

Skin contact Acts as a defatting agent on skin. May cause cracking of skin, and eczema.

Eye contact May cause eye and respiratory system irritation.

Route of entry Skin and/or eye contact Inhalation

Target organs Central nervous system

1,2,4-TRIMETHYLBENZENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 6,900.0

Species Mouse

ATE oral (mg/kg) 6,900.0

Serious eye damage/irritation

Serious eye damage/irritation Causes eye irritation

Respiratory sensitisation

2 PK EPOXY FINISH BASE

Respiratory sensitisation	No specific test data are available.
<u>Skin sensitisation</u>	
Skin sensitisation	Irritating
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No data available.
Genotoxicity - in vivo	No data available.
<u>Carcinogenicity</u>	
Carcinogenicity	No information available.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No information available.
Reproductive toxicity - development	No information available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No information available.
<u>Aspiration hazard</u>	
Aspiration hazard	No information available.
<u>General information</u>	
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Harmful by inhalation.
Ingestion	Harmful if swallowed.
Skin contact	Irritating to skin.
Eye contact	Harmful in contact with eyes.
Route of entry	Inhalation Ingestion Skin and/or eye contact Oral

CUMENE

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,400.0

Species Rat

ATE oral (mg/kg) 1,400.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 8,000.0

2 PK EPOXY FINISH BASE

Species	Rat
ATE inhalation (vapours mg/l)	8,000.0
<u>Serious eye damage/irritation</u>	
Serious eye damage/irritation	Causes eye irritation
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	No specific test data are available.
<u>Skin sensitisation</u>	
Skin sensitisation	Irritating
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No information available.
Genotoxicity - in vivo	No information available.
<u>Carcinogenicity</u>	
Carcinogenicity	No evidence of carcinogenicity
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No information available.
Reproductive toxicity - development	No information available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No specific test data are available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No specific test data are available.
<u>Aspiration hazard</u>	
Aspiration hazard	No information available.
<u>General information</u>	
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Harmful by inhalation.
Ingestion	Harmful if swallowed.
Skin contact	Irritating to skin.
Eye contact	Harmful in contact with eyes.
Route of entry	Ingestion Inhalation Oral Skin and/or eye contact

ETHYLBENZENE

Serious eye damage/irritation

2 PK EPOXY FINISH BASE

Serious eye damage/irritation	Harmful in contact with eyes and skin. Causes eye irritation
<u>Respiratory sensitisation</u>	
Respiratory sensitisation	Irritating to respiratory system.
<u>Skin sensitisation</u>	
Skin sensitisation	Slightly irritating to the skin.
<u>Germ cell mutagenicity</u>	
Genotoxicity - in vitro	No information available.
Genotoxicity - in vivo	No specific test data are available.
<u>Carcinogenicity</u>	
Carcinogenicity	No specific test data are available.
<u>Reproductive toxicity</u>	
Reproductive toxicity - fertility	No information available.
Reproductive toxicity - development	No information available.
<u>Specific target organ toxicity - single exposure</u>	
STOT - single exposure	No information available.
<u>Specific target organ toxicity - repeated exposure</u>	
STOT - repeated exposure	No information available.
<u>Aspiration hazard</u>	
Aspiration hazard	May be harmful if swallowed and enters airways.
<u>General information</u>	
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Harmful by inhalation.
Ingestion	Harmful if swallowed.
Skin contact	Harmful in contact with skin.
Eye contact	Harmful in contact with eyes.
Route of entry	Ingestion Inhalation Oral Skin and/or eye contact

WHITE SPIRIT

Toxicological effects	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. High vapour concentrations can cause headaches, dizziness and nausea.
<u>Acute toxicity - oral</u>	

2 PK EPOXY FINISH BASE

Acute toxicity oral (LD₅₀ mg/kg) 15,001.0

Species Rat

ATE oral (mg/kg) 15,001.0

Acute toxicity - dermal

Acute toxicity dermal (LD₅₀ mg/kg) 3,401.0

Species Rat

ATE dermal (mg/kg) 3,401.0

Acute toxicity - inhalation

Acute toxicity inhalation (LC₅₀ vapours mg/l) 13,101.0

Species Rat

ATE inhalation (vapours mg/l) 13,101.0

Serious eye damage/irritation

Serious eye damage/irritation Not Irritating

Respiratory sensitisation

Respiratory sensitisation Not determined.

Skin sensitisation

Skin sensitisation Not sensitising.

Germ cell mutagenicity

Genotoxicity - in vitro Negative.

Genotoxicity - in vivo Negative.

Carcinogenicity

Carcinogenicity Not classified carcinogenic

Reproductive toxicity

Reproductive toxicity - fertility No information available.

Reproductive toxicity - development No evidence of development toxicity

Specific target organ toxicity - single exposure

STOT - single exposure No specific test data are available.

Target organs Central nervous system Vapours can cause drowsiness & dizziness.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure No specific test data are available.

2 PK EPOXY FINISH BASE

Aspiration hazard

Aspiration hazard No information available.

General information

Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.

Inhalation

Vapours may irritate throat and respiratory system and cause headache, dizziness and dullness.

Ingestion

This product is moderately irritating. Irritating. May cause nausea, stomach pain and vomiting.

Skin contact

May cause irritation.

Eye contact

May cause severe eye irritation.

Route of entry

Skin and/or eye contact

Target organs

Central nervous system

Medical symptoms

No specific information available.

SECTION 12: Ecological Information

12.1. Toxicity

Toxicity This product contains substances which are harmful to aquatic organisms. Do not discharge into drains, water courses or onto the ground.

Ecological information on ingredients.

1,2,4-TRIMETHYLBENZENE

Toxicity

This product contains substances which are harmful to aquatic organisms. Do not discharge into drains, water courses or onto the ground.

Acute toxicity - fish

, LC50 96 hours 77.2 mg/lit (Flathead Minnow) : LC50 96 hours 8.6 mg/lit (Japanese medaka 9Oryzias latipes) ,

Acute toxicity - aquatic invertebrates

, LC50 50 mg/lit (Water flea - Daphnia magna) : EC50 24 hours (static) 50 mg/lit (Water flea - Daphnia magna) ,

Acute toxicity - aquatic plants

, EC50 48 hours 25 mg/lit (Alga - Scenedesmus sp.) : ,

Acute toxicity - microorganisms

No information available.

Acute toxicity - terrestrial

No information available.

Mesitylene

Toxicity

This product contains substances which are harmful to aquatic organisms. Do not discharge into drains, water courses or onto the ground.

Acute toxicity - fish

, LC50 96 hours 3.48 mg/lit (Flathead Minnow) : LC 50 96 hours 12.5 - 13 mg/lit (Goldfish) ,

2 PK EPOXY FINISH BASE

Acute toxicity - aquatic invertebrates , EC650 72 hours 50 mg/lit (Water flea Daphnia) : ,

Acute toxicity - aquatic plants No information available.

Acute toxicity - microorganisms No information available.

Acute toxicity - terrestrial , LC50 72 hours 13.7 mg/lit (Goldfish - unspecified) : ,

12.2. Persistence and degradability

Persistence and degradability Solvent will evaporate, residue will not readily biodegrade. There are no data on the degradability of this product.

Ecological information on ingredients.

1,2,4-TRIMETHYLBENZENE

Persistence and degradability No data available.

Biodegradation No data available.

MESITYLENE

Persistence and degradability The product is not readily biodegradable.

Biodegradation Not readily biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential The product contains potentially bioaccumulating substances.

Partition coefficient Not available.

Ecological information on ingredients.

1,2,4-TRIMETHYLBENZENE

Bioaccumulative potential No data available on bioaccumulation.

MESITYLENE

Bioaccumulative potential Low potential for bioaccumulation.

12.4. Mobility in soil

Mobility The product is insoluble in water. Mobile liquid, solvent will evaporate leaving a semi-solid mass.

Ecological information on ingredients.

1,2,4-TRIMETHYLBENZENE

Mobility No information available.

MESITYLENE

2 PK EPOXY FINISH BASE

Mobility No information available.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

Ecological information on ingredients.

1,2,4-TRIMETHYLBENZENE

Results of PBT and vPvB assessment No data available.

MESITYLENE

Results of PBT and vPvB assessment This product does not contain any substances classified as PBT or vPvB.

12.6. Other adverse effects

Other adverse effects Not known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

General information Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. This material and its container must be disposed of in a safe way. The generation of waste should be minimised or avoided wherever possible. The company encourages the recycle, recovery and reuse of materials, wherever possible.

Disposal methods Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Dispose of waste via a licensed waste disposal contractor. Dispose of contents/container in accordance with national regulations.

SECTION 14: Transport information

General To avoid the risk of spillage, always store and transport in a secure, upright position. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.1. UN number

UN No. (ADR/RID) 1263

UN No. (IMDG) 1263

UN No. (ICAO) 1263

UN No. (ADN) 1263

14.2. UN proper shipping name

Proper shipping name (ADR/RID) PAINT

Proper shipping name (IMDG) PAINT

Proper shipping name (ICAO) PAINT

Proper shipping name (ADN) PAINT

2 PK EPOXY FINISH BASE

14.3. Transport hazard class(es)

ADR/RID class	3
ADR/RID classification code	F1
ADR/RID label	3
IMDG class	3
ICAO class/division	3
ADN class	3

Transport labels



14.4. Packing group

ADR/RID packing group	III
IMDG packing group	III
ADN packing group	III
ICAO packing group	III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No.

14.6. Special precautions for user

EmS	F-E, S-E
ADR transport category	3
Emergency Action Code	•3YE
Hazard Identification Number (ADR/RID)	33
Tunnel restriction code	(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972. Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste) Regulations 1980 (as amended). Control of Substances Hazardous to Health Regulations 2002 (as amended).
----------------------	---

2 PK EPOXY FINISH BASE

EU legislation

Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).

Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).

Commission Regulation (EU) No 453/2010 of 20 May 2010.

Guidance

Workplace Exposure Limits EH40.

Introduction to Local Exhaust Ventilation HS(G)37.

CHIP for everyone HSG228.

Approved Classification and Labelling Guide (Sixth edition) L131.

Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information	Product to be used in industrial and/or professional applications.
Issued by	BOD
Revision date	24/02/2015
Revision	0
SDS number	10964
Risk phrases in full	<p>R10 Flammable.</p> <p>R11 Highly flammable.</p> <p>R20 Harmful by inhalation.</p> <p>R20/21 Harmful by inhalation and in contact with skin.</p> <p>R22 Harmful if swallowed.</p> <p>R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.</p> <p>R34 Causes burns.</p> <p>R36/37/38 Irritating to eyes, respiratory system and skin.</p> <p>R36/38 Irritating to eyes and skin.</p> <p>R37 Irritating to respiratory system.</p> <p>R37/38 Irritating to respiratory system and skin.</p> <p>R38 Irritating to skin.</p> <p>R39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.</p> <p>R40 Limited evidence of a carcinogenic effect.</p> <p>R41 Risk of serious damage to eyes.</p> <p>R43 May cause sensitisation by skin contact.</p> <p>R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.</p> <p>R65 Harmful: may cause lung damage if swallowed.</p> <p>R66 Repeated exposure may cause skin dryness or cracking.</p> <p>R67 Vapours may cause drowsiness and dizziness.</p>

2 PK EPOXY FINISH BASE

Hazard statements in full

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H301 Toxic if swallowed.
H302 Harmful if swallowed.
H304 May be fatal if swallowed and enters airways.
H311 Toxic in contact with skin.
H312 Harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H351 Suspected of causing cancer.
H372 Causes damage to organs through prolonged or repeated exposure.
H373 May cause damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.

The product should not be used for the purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.