

# EUR Version 3.0 - Not Valide Without Verified Date

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier	
Product code :	DS311A8266
Product Name :	.PE50 RAL 7026 5AH
1.2 Relevant identified uses of the substance or mixture and us	es advised against
Identified uses :	Powder Coating for professional use.
1.3 Details of the supplier of the safety data sheet	
Company :	Oxyplast Belgium N.V. Hulsdonk 35, Havennr. 4250 H B-9042, Gent-Mendonk
Telephone number :	+32 9 326 79 20
FAX :	+32 9 337 01 59
E-mail :	info@oxyplast.be
1.4 Emergency telephone number	
Oxyplast: +32 9 326 79 20 (only available during office hours)	

# **SECTION 2: Hazards identification**

### 2.1 Classification of the substance or mixture

This preparation is not classified as dangerous according to Regulation (EC) No. 1272/2008 [CLP/GHS].

### 2.2 Label elements

Labelling according to Regulation (EC) 1272/2008 (CLP): Hazard Pictogram(s)

No danger Pictogram

### Signal word

No signal word

# Supplemental label elements

piciliciilai label el	
EUH208	Contains Bis(2,3-epoxypropyl) terephthalate. May produce an allergic reaction.
EUH208	Contains Tris(oxiranylmethyl) benzene-1,2,4-tricarboxylate. May produce an allergic reaction.
EUH210	Safety data sheet available on request.

### 2.3 Other hazards

No.

# **SECTION 3: Composition/information on ingredients**

### 3.2 Mixtures

Substances presenting a health or environmental hazard within the meaning of the Regulation (EC) No. 1272/2008 [CLP/GHS]. Hazardous Ingredient (\*)

Components Name	Identifiers	Percentage :	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Bis(2,3-epoxypropyl) terephthalate	CAS No.: 7195-44-0 EC-No.: 230-565-0 REACH Registration N°: 01- 2119909640-43-XXXX	< 0.4 %	Skin Irrit. 2, H315 Skin Sens. 1, H317 Eye Dam. 1, H318
Tris(oxiranylmethyl) benzene-1,2,4- tricarboxylate	CAS No.: 7237-83-4 EC-No.: 230-638-7 REACH Registration N° : 01- 2119912714-41-XXXX	< 0.2 %	Skin Sens. 1, H317 Eye Irrit. 2, H319

(\*) See Section 16 for full text of Hazard Statements.

 PROTECH CHEMICALS LTD.
 PROTECH-OXYPLAST CZ
 PROTECH CHEMICALS LTD.
 PROTECH POWDER COATINGS INC.
 PROTECH DO BRASIL LTDA.
 PROTECH MEXICANA S.A. DE

 ST.LAURENT, QC (CANADA)
 OPAVA,
 NORTH YORK, ON (CANADA)
 FAIRFIELD, NJ, USA
 GAURULHOS/SP, BRAZIL
 C.V. MEXICO, D.F.

 VORK / ERIE, PA, USA
 YORK / ERIE, PA, USA
 YORK / ERIE, PA, USA
 YORK / ERIE, PA, USA
 C.V. MEXICO, D.F.

according to 1907/2006/EC (REACH), 1272/2008/EC (CLP), and GHS

> Print Date : Verified Date :

3-SEP-2015 3-SEP-2015

1/5

# **SECTION 4: First aid measures**

### 4.1 Description of first aid measures

In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person. If unconscious place in recovery position and seek medical advice.

### Inhalation

Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration.

### Skin contact

Remove contaminated clothing. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do NOT use solvents or thinners. **Eve contact** 

Remove contact lenses, irrigate copiously with clean, fresh water, holding the eyelids apart for at least 10 minutes and seek immediate medical advice.

### Ingestion

If accidentally swallowed rinse the mouth with plenty of water (only if the person is conscious) and obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.

# 4.2 Most important symptoms and effects, both acute and delayed

No description of any toxic symptoms.

**4.3 Indication of any immediate medical attention and special treatment needed** No information available.

# **SECTION 5: Firefighting measures**

### 5.1 Extinguishing media

Suitable extinguishing media : Unsuitable extinguishing media : Alcohol resistant foam, CO2, powders, water spray. inert gas under high pressure (e.g. CO2), water jet.

### 5.2 Special hazards arising from the substance or mixture

Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required.

### 5.3 Advice for firefighters

Cool closed containers exposed to fire with water. Do not allow run-off from fire fighting to enter drains or water courses.

# **SECTION 6: Accidental release measures**

### 6.1 Personal precautions, protective equipment and emergency procedures

Exclude sources of ignition and ventilate the area. Avoid breathing dust. Refer to protective measures listed in sections 7 and 8.

### 6.2 Environmental precautions

Do not allow to enter drains or watercourses. If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations.

#### 6.3 Methods and material for containment and cleaning up

Contain and collect spillage with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13). Do not use a dry brush as dust clouds or static can be created.

### 6.4 Reference to other sections

Sections 7, 8 and 13.

# **SECTION 7: Handling and storage**

# Advice should be taken from a competent occupational health practitioner on the assessment of employees with skin or respiratory complaints before the individual is exposed to the uncured product.

### 7.1 Precautions for safe handling

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Electrical equipment and lighting should be protected to appropriate standards to prevent dust coming into contact with hot surfaces, sparks or other ignition sources. Preparation may charge electro statically: always use earthing leads when transferring from one container to another. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates and spray mist arising from the application of this preparation. Avoid inhalation of dust from sanding. Smoking, eating and drinking should be prohibited in application area. Comply with the health and safety at work laws.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Additional information on storage conditions

Observe label precautions. Store between 5 °C and 25 °C in a dry, well ventilated place away from sources of heat and direct sunlight. Keep container tightly closed. No smoking. Prevent unauthorised access. Containers which are opened must be carefully resealed and kept upright to prevent leakage.

#### 7.3 Specific end use(s)

Powder Coatings.

# SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Limits for occupational exposure and / or biological limit values : DNEL and PNEC values :

Control banding :

# 8.2 Exposure controls

### Appropriate engineering controls

Avoid inhalation of dusts. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates below the OEL, suitable respiratory protection must be worn.

Not available.

Not available.

No hazardous ingredient.

### Occupational exposure controls

### **Respiratory protection**

If workers are exposed to concentrations above the exposure limit they must use appropriate, certified respirators.

### Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals. For prolonged or repeated handling, use appropriate protective gloves. The breakthrough time must be greater than the end use time of the product. The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed. Gloves should be replaced regularly and if there is any sign of damage to the glove material. Always ensure that gloves are free from defects and that they are stored and used correctly. The performance or effectiveness of the glove may be reduced by physical/ chemical damage and poor maintenance. Barrier creams may help to protect the exposed areas of the skin, but are not substitutes for full physical protection. They should however not be applied once exposure has occurred.

### eye protection

Safety eye-wear should be used when there is a likelihood of exposure.

### Skin protection

Personnel should wear protective clothing. Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder are avoided.

### Environmental exposure controls

Do not allow to enter drains or water courses.

# **SECTION 9: Physical and chemical properties**

9.1 Information on basic physical and chemical properties	
Physical state :	Fine Powder
Colour :	Gray
Odour :	None.
Odour threshold :	Not applicable.
pH :	Not applicable.
Melting range :	80 - 110 ℃
Initial boiling point and boiling range :	Not applicable.
Flash point :	Not applicable.
Evaporation rate :	Not applicable.
Flammability (solid, gas) :	Not applicable.
Upper/lower flammability or explosive limits :	35 - 70 g/m³
Vapour pressure :	Not applicable.
Vapour density :	Not applicable.
Relative density :	1.2 - 1.9 g/cm <sup>3</sup>
Solubility(ies) :	Insoluble in water.
Partition coefficient: n-octanol/water :	Not applicable.
Auto-ignition temperature :	>450 °C
Oxidising properties :	Not applicable.
9.2 Other information	
Minimum ignition energy: :	5 mJ (without inductance)

### **SECTION 10: Stability and reactivity**

### 10.1 Reactivity

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

### 10.2 Chemical stability

Stable under recommended storage and handling conditions (see section 7).

#### 10.3 Possibility of hazardous reactions

When exposed to high temperatures may produce hazardous decomposition products such as carbon monoxide and dioxide, smoke, oxides of nitrogen.

### 10.4 Conditions to avoid

When exposed to high temperatures may produce hazardous decomposition products.

### 10.5 Incompatible materials

None.

### 10.6 Hazardous decomposition products

such as carbon monoxide and dioxide, smoke, oxides of nitrogen etc.

# **SECTION 11: Toxicological information**

There are no data available on the mixture itself. The mixture has been assessed following the method of the Regulation (EC) No. 1272/2008 [CLP/GHS] and classified for toxicological hazards accordingly. See Sections 2 and 3 for details.

# **SECTION 12: Ecological information**

There are no data available on the mixture itself. Coatings powder residues should not be allowed to enter drains or water courses or be deposited where they can affect ground or surface waters.

12.1 Toxicity

No data available.

- 12.2 Persistence and degradability
- No data available.
- 12.3 Bioaccumulative potential
- No data available.

12.4 Mobility in soil

- No data available.
- 12.5 Results of PBT and vPvB assessment No data available.
- 12.6 Other adverse effects

Not available.

### **SECTION 13: Disposal considerations**

### 13.1 Waste treatment methods

Do not allow to enter drains or water courses. The European Waste Catalogue classification of this product, when disposed of as waste, is Waste Code: Powder coatings: 08 02 01 (according to Directive 2000/532/EC): If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned. For further information contact your local waste authority. Using information provided in this safety data sheet, advice should be obtained from the local waste authority on the classification of empty containers. Empty containers must be scrapped or reconditioned. Dispose of containers contaminated by the product in accordance with local or national legal provisions.

# **SECTION 14: Transport information**

14.1 UN number	
Not applicable.	
14.2 UN proper shipping name	
Not applicable.	
14.3 Transport hazard class(es)	
Not available.	
14.4 Packing group	
Not applicable.	
14.5 Environmental hazards	
IMDG Code	
Marine Pollutant :	Not applicable.
Marine Pollutant substance :	Not applicable.
14.6 Special precautions for user	
Transport within the user's premises: :	Always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.
14.7 Transport in bulk according to Annex II of MARPO	
Not applicable.	
Additional information for Transport in accordance	with IMDG, ADR/RID and ICAO/IATA
IMDG Code	
Emergency Schedule Number :	Not applicable.
Viscous substances up to 30 litre packs :	Not applicable.
ADR/RID (additional information)	
Viscous substances up to 450 litre packs :	Not applicable.
ICAO/IATA (additional information)	
Viscous substances :	Not applicable.
The "viscosity exemption" provision does not apply to a	

03-sept-15

# **SECTION 15: Regulatory information**

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

The information in this Safety Data Sheet is required pursuant to Directive 67/548/EEC or Directive 1999/45/EC Not applicable.

Other requirements, restrictions and ban regulations :

# 15.2 Chemical safety assessment

No Chemical Safety Assessment has been carried out for this mixture by the supplier.

# **SECTION 16: Other information**

### 16.1 Full text of Hazard Statements appearing in section 3

### Hazard Statement(s)

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.

### **Further Information**

The details in this material safety data sheet satisfy national and EU legislation. We have no knowledge or control over the user's working conditions however. The product may not be used for any purpose other than that specified in chapter 1 unless written consent has been obtained. The user is responsible for the observance of all required statutory provisions.

03-sept-15