## **Safety Data Sheet**

Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH)

Revision Date 12-Sep-2022 Version 61 Supercedes Date: 27-Sep-2021

# Section 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

## 1.1. Product Identifier

Product code 14662

Product name PE/P/Q FTX BEIGE RAL 1002 HR

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use Paint, Coatings

## 1.3. Details of the supplier of the safety data sheet

See section 16 for more information

The Valspar (Switzerland) Corporation AG European Headquarters Rosengartenstrasse 25 8608 Bubikon CH-SWITZERLAND Only Representative (OR) for imports only:

Valspar B.V. Zuiveringweg 89 8243 PE Lelystad The Netherlands

GPSReach@sherwin.com

Member Company of Sherwin Williams

For further information, please contact

E-mail address <a href="mailto:sdshelpdesk@valspareurope.com">sdshelpdesk@valspareurope.com</a>

## 1.4. Emergency telephone number

24 Hour Emergency Phone Number

24 Hour Linergency	Hone Humber			
International	<b>Austria</b>	<b>Belgium</b>	<b>Bulgaria</b>	<b>Croatia</b>
+1 703 741 5971	+(43)-13649237	+(32)-28083237	+(359)-32570104	+(385)-17776920
Czech Republic	<b>Denmark</b>	Estonia	Finland	France
+(420)-228880039	+(45)-69918573	+(372)-6681294	+(358)-942419014	+(33)-975181407
<b>Germany</b> 0800-181-7059	<b>Greece</b>	Hungary	Ireland	<b>Italy</b>
	+(30)-2111768478	+(36)-18088425	+(353)-19014670	800-789-767
<b>Latvia</b>	Lithuania	Luxembourg	Netherlands	<b>Norway</b>
+(371)-66165504	+(370)-52140238	+(352)-20202416	+(31)-858880596	+(47)-21930678
Poland	Portugal	Romania	<b>Slovakia</b>	<b>Slovenia</b>
+(48)-223988029	+(351)-308801773	(+40)-37-6300026	+(421)-233057972	+(386)-18888016
<b>Spain</b>	<b>Sweden</b>	Switzerland	United Kingdom	
900-868538	+(46)-852503403	+(41)- 435082011	+(44)-870-8200418	

## Poison control centre phone number

Only for the purpose of informing medical personnel in cases of acute intoxication

Belgium	Denmark	France	Finland	Hungary
+32 70 245 245	+45 82 12 12 12	+33 (0) 1454 25959	+358 9 471977	+36-80-20-11-99
lceland +354 543 2222	Ireland +353 (0)1 809 2166 (8.00 - 22.00)	Lithuania +370 (85) 2362052	Netherlands +31 (0) 88-755 8000	<b>Norway</b> +47 22 59 13 00
<b>Portugal</b> +(351) 800 250 250	<b>Slovakia</b> +421 2 5477 4166	<b>Spain</b> +3415620420	Sweden +46 8 33 12 31 (M-F 9.00-17.00)	

## Section 2: HAZARDS IDENTIFICATION

## 2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Chronic Aquatic Toxicity Category 3 - (H412)

#### 2.2. Label Elements

## Labelling according to Regulation (EC) No. 1272/2008 [CLP]

#### **Hazard statements**

H412 - Harmful to aquatic life with long lasting effects

EUH210 - Safety data sheet available on request

EUH212 - Warning! Hazardous respirable dust may be formed when used. Do not breathe dust.

## PRECAUTIONARY STATEMENTS - EU (§28, 1272/2008)

P202 - Do not handle until all safety precautions have been read and understood

P233 - Keep container tightly closed

P273 - Avoid release to the environment

P308 + P313 - IF exposed or concerned: Get medical advice/attention

P391 - Collect spillage

P501 - Dispose of contents/ container to an approved waste disposal plant

#### 2.3. Other Hazards

## Section 3: COMPOSITION/INFORMATION ON INGREDIENTS

#### 3.2. Mixtures

Chemical name	CAS No	Weight-%	EC No	Classification according to Regulation (EC) No. 1272/2008 [CLP]	REACH registration number	Note:
C.I. Pigment Yellow 53	8007-18-9	1 - < 3	232-353-3	NE	01-2119491302-44	A,1
Propanedioic acid, [[3,5-bis(1,1-dimethyleth yl)-4-hydroxyphenyl]met hyl]butyl-, bis(1,2,2,6,6-pentameth yl-4-piperidinyl) ester		0.1 - < 0.3	264-513-3	STOT RE 1 (H372) Acute Tox. 4 (H302) Aquatic Chronic 1 (H410)	01-2119978231-37	-

## Full text of H- and EUH-phrases: see section 16

#### **Additional information**

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment, are PBTs or vPvBs or have been assigned a workplace exposure limit and hence require reporting in this section.

## **Section 4: FIRST AID MEASURES**

## 4.1. Description of first aid measures

## **General Advice**

IF exposed or concerned: Get medical advice/attention

## Eye Contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

If eye irritation persists: Get medical advice/attention

#### Skin contact

Rinse skin with water/shower

If skin irritation occurs: Get medical advice/attention

#### **INHALATION**

IF INHALED: Call a POISON CENTER or doctor if you feel unwell

#### **INGESTION**

Do NOT induce vomiting

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

## 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms** No information available.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Note to doctors Treat symptomatically

## **Section 5: FIRE FIGHTING MEASURES**

## 5.1. Extinguishing media

## **Suitable Extinguishing Media**

Water spray (fog) Carbon dioxide (CO2) Alcohol resistant foam Dry chemical

## Not to be used for safety reasons:

Inert gas under high pressure (e.g. CO2), water jet ( Do not use if package is open or torn )

## 5.2. Special hazards arising from the substance or mixture

Burning produces heavy smoke Fire may produce irritating and/or toxic gases In the event of fire and/or explosion do not breathe fumes

## 5.3. Advice for firefighters

Wear self-contained breathing apparatus and protective suit Cool containers with flooding quantities of water until well after fire is out Do not allow run-off from fire-fighting to enter drains or water courses

## Section 6: ACCIDENTAL RELEASE MEASURES

## 6.1. Personal precautions, protective equipment and emergency procedures

## **Personal Precautions**

Remove all sources of ignition
Do not breathe dust
Use personal protective equipment as required
Keep people away from and upwind of spill/leak
Avoid contact with skin, eyes or clothing

#### For emergency responders

Use personal protection recommended in Section 8

#### 6.2. Environmental precautions

Do not allow into any sewer, on the ground or into any body of water
If the product contaminates lakes, rivers or sewage, inform appropriate authorities in accordance with local regulations
Prevent further leakage or spillage if safe to do so

Local authorities should be advised if significant spillages cannot be contained

#### 6.3. Methods and material for containment and cleaning up

#### **Methods for Containment**

Prevent further leakage or spillage if safe to do so

#### **Methods for Cleaning Up**

Dispose of waste product or used containers according to local regulations

Do not use a dry brush as dust clouds or static can be created

Dam up

Pick up and transfer to properly labelled containers

Clean contaminated surface thoroughly

Contain and collect spillage with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations (see section 13)

#### 6.4. Reference to other sections

See Section 8 for information on appropriate personal protective equipment

See Section 13 for additional waste treatment information

## **Section 7: HANDLING AND STORAGE**

#### 7.1. Precautions for safe handling

#### Advice on safe handling

Precautions should be taken to prevent the formation of dusts in concentrations above flammable, explosive or occupational exposure limits. Operators should wear anti-static footwear and clothing and floors should be of the conducting type. Use personal protection recommended in Section 8. Comply with the health and safety at work laws. Prevent product from entering drains. Use only with adequate ventilation. Do not breathe dust/fume/gas/mist/vapours/spray.

#### **General hygiene considerations**

When using do not eat, drink or smoke. Wash contaminated clothing before reuse. Avoid contact with skin, eyes or clothing.

## 7.2. Conditions for safe storage, including any incompatibilities

#### **Storage Conditions**

Keep/store only in original container. Store in accordance with local regulations. Keep unauthorised personnel away. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Keep container tightly closed in a dry and well-ventilated place.

## Incompatible materials

Strong oxidising agents

## 7.3. Specific end use(s)

Recommended use

## Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1. Control parameters

#### **Exposure Limits**

If  $S^{\star}$  appears in the OEL table, it indicates this chemical contains a skin notation.

**Paint Coatings** 

Chemical name	European Union	Austria	Belgium	Bulgaria	Czech Republic	Denmark	Estonia
Titanium dioxide 13463-67-7	- Cilion	STEL 10 mg/m³ alveolar dust, respirable fraction TWA: 5 mg/m³ alveolar dust, respirable fraction	TWA: 10 mg/m <sup>3</sup>	TWA: 10.0 mg/m³ respirable dust		TWA: 6 mg/m <sup>3</sup>	TWA: 5 mg/m <sup>3</sup>
C.I. Pigment Brown 24 68186-90-3		STEL 1.5 mg/m <sup>3</sup> inhalable fraction TWA: 0.5 mg/m <sup>3</sup> inhalable	mg/m³ Sb	TWA: 0.5 mg/m <sup>3</sup>	Ceiling: 1.5 mg/m³ TWA: 0.5 mg/m³	TWA: 0.5 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>

	fraction					
Barium sulfate		TWA: 10 mg/m <sup>3</sup>				
7727-43-7			mg/m³			
Talc	TWA: 2 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>	TWA: 1.0	TWA: 2.0 mg/m <sup>3</sup>	TWA: 0.3	TWA: 1 mg/m <sup>3</sup>
14807-96-6	respirable		fiber/cm3		fiber/cm3	total dust
	fraction		respirable			TWA: 0.5 mg/m <sup>3</sup>
			fraction, fibers			respirable dust
			TWA: 6.0 mg/m <sup>3</sup>			
			inhalable			
			fraction			
			TWA: 3.0 mg/m <sup>3</sup>			
			respirable			
			fraction			
C.I. Pigment Yellow 53	STEL 1.5 mg/m <sup>3</sup>	TWA: 0.5	TWA: 0.5 mg/m <sup>3</sup>	Ceiling: 1.5	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.1 mg/m <sup>3</sup>
8007-18-9	inhalable	mg/m³ Sb TWA:	TWA: 0.05	mg/m³ Ceiling:		
	fraction	0.2 mg/m <sup>3</sup> Ni	mg/m³	0.25 mg/m <sup>3</sup>		
	TWA: 0.5 mg/m <sup>3</sup>			TWA: 0.5 mg/m <sup>3</sup>		
	inhalable			TWA: 0.05		
	fraction			mg/m³		

Chemical name	Finland	France	Germany	Greece	Hungary	Iceland	Ireland
Titanium dioxide 13463-67-7		TWA: 10 mg/m <sup>3</sup>		TWA: 10 mg/m³ inhalable fraction TWA: 5 mg/m³ respirable fraction		Ceiling: 12 mg/m³ TWA: 6 mg/m³	TWA: 10 mg/m³ total inhalable dust TWA: 4 mg/m³ respirable dust STEL: 30 mg/m³ total inhalable dust STEL: 12 mg/m³ respirable dust
C.I. Pigment Brown 24 68186-90-3	TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	TWA: 2 mg/m³ inhalable fraction	TWA: 0.5 mg/m³ Sb TWA: 0.5 mg/m³ Cr	STEL: 2 mg/m <sup>3</sup> TWA: 0.5 mg/m <sup>3</sup> TWA: 2 mg/m <sup>3</sup>	Ceiling: 1 mg/m³ TWA: 0.5 mg/m³	TWA: 0.5 mg/m³ TWA: 2 mg/m³ STEL: 1.5 mg/m³ STEL: 6 mg/m³
Barium sulfate 7727-43-7			TWA: 4 mg/m³ inhalable fraction TWA: 1.5 mg/m³ respirable fraction Ceiling / Peak: 2.4 mg/m³ respirable fraction				TWA: 2 mg/m³ respirable dust STEL: 6 mg/m³ respirable dust
Talc 14807-96-6	TWA: 0.5 fiber/cm3 fiber STEL: 2 ppm granular form, inhalable dust STEL: 1 ppm granular form, respirable			TWA: 10 mg/m³ inhalable fraction TWA: 2 mg/m³ respirable fraction	TWA: 2 mg/m <sup>3</sup> respirable		total inhalable dust STEL: 2.4 mg/m³ respirable dust
C.I. Pigment Yellow 53 8007-18-9	TWA: 0.5 mg/m³ TWA: 0.05 mg/m³ inhalable dust TWA: 0.01 mg/m³ respirable	TWA: 0.5 mg/m <sup>3</sup>		TWA: 0.5 mg/m³ Sb TWA: 1 mg/m³ Ni	Ceiling: 0.01 mg/m³ STEL: 2 mg/m³ TWA: 0.5 mg/m³	Ceiling: 1 mg/m³ TWA: 0.5 mg/m³	TWA: 0.5 mg/m³ STEL: 1.5 mg/m³

Chemical name	Italy	Latvia	Luxembourg	Netherlands	Norway	Poland	Portugal
Titanium dioxide		TWA: 10 mg/m <sup>3</sup>			TWA: 5 mg/m <sup>3</sup>	STEL: 30 mg/m <sup>3</sup>	TWA: 10 mg/m <sup>3</sup>
13463-67-7					STEL: 10 mg/m <sup>3</sup>	TWA: 10.0	
						mg/m³ inhalable	
						fraction	
C.I. Pigment Brown 24		TWA: 2 mg/m <sup>3</sup>		TWA: 0.5 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>	STEL: 30 mg/m <sup>3</sup>	TWA: 0.5 mg/m <sup>3</sup>
68186-90-3					STEL: 1.5	TWA: 0.5 mg/m <sup>3</sup>	

			mg/m³	TWA: 10 mg/m <sup>3</sup>	
Barium sulfate			TWA: 0.5 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>
7727-43-7			STEL: 1.5		
			mg/m³		
Talc		TWA: 0.25	TWA: 6 mg/m <sup>3</sup>	TWA: 4.0 mg/m <sup>3</sup>	TWA: 2 mg/m <sup>3</sup>
14807-96-6		mg/m³	total dust	inhalable	respirable
			TWA: 2 mg/m <sup>3</sup>	fraction	fraction,
				TWA: 1.0 mg/m <sup>3</sup>	particulate
			STEL: 12 mg/m <sup>3</sup>	respirable	matter
			total dust	fraction	containing no
			STEL: 4 mg/m <sup>3</sup>		Asbestos and
			respirable dust		<1% Crystalline
					silica
C.I. Pigment Yellow 53	TWA: 0.05	TWA: 0.5 mg/m <sup>3</sup>		STEL: 30 mg/m <sup>3</sup>	
8007-18-9	mg/m³		TWA: 0.05	TWA: 0.5 mg/m <sup>3</sup>	
			mg/m³	TWA: 0.25	
			STEL: 1.5	mg/m³ TWA: 10	
			mg/m³ STEL:	mg/m³	
			0.15 mg/m <sup>3</sup>		

Chemical name	Romania	Slovakia	Slovenia	Spain	Sweden	Switzerland	United Kingdom
Titanium dioxide 13463-67-7	TWA: 10 mg/m³ STEL: 15 mg/m³			TWA: 10 mg/m <sup>3</sup>	TLV/LLV: 5 mg/m³ total dust	TWA: 3 mg/m <sup>3</sup> respirable dust	STEL: 30 mg/m³ total inhalable STEL: 12 mg/m³ respirable TWA: 10 mg/m³ total inhalable TWA: 4 mg/m³ respirable
C.I. Pigment Brown 24 68186-90-3		Ceiling: 1.0 mg/m³ TWA: 0.5 mg/m³ total dust	inhalable	TWA: 0.5 mg/m <sup>3</sup>	TLV/LLV: 0.25 mg/m³ Sb total inhalable dust TLV/LLV: 0.5 mg/m³ Cr total dust	TWA: 0.5 mg/m³ inhalable dust	STEL: 1.5 mg/m³ TWA: 0.5 mg/m³
Barium sulfate 7727-43-7		TWA: 1.5 mg/m <sup>3</sup>		TWA: 10 mg/m <sup>3</sup>			STEL: 30 mg/m³ inhalable dust STEL: 12 mg/m³ respirable dust TWA: 10 mg/m³ inhalable dust TWA: 4 mg/m³ respirable dust
Talc 14807-96-6	TWA: 2 mg/m <sup>3</sup> dust, inhalable fraction	TWA: 2 mg/m³ respirable fraction, 5% or less fibrogenic component TWA: 10 mg/m³ respirable fraction, greater than 5% fibrogenic component TWA: 10 mg/m³ total aerosol	TWA: 2 mg/m <sup>3</sup> respirable fraction	TWA: 2 mg/m <sup>3</sup> respirable fraction	TLV/LLV: 2 mg/m³ total dust TLV/LLV: 1 mg/m³ respirable dust	TWA: 2 mg/m <sup>3</sup> respirable dust	STEL: 3 mg/m <sup>3</sup> respirable dust TWA: 1 mg/m <sup>3</sup> respirable dust
C.I. Pigment Yellow 53 8007-18-9	TWA: 0.1 mg/m³ STEL: 0.5 mg/m³	Ceiling: 1.0 mg/m³ TWA: 0.5 mg/m³ total dust	TWA: 0.5 mg/m³ inhalable fraction TWA: 0.05 mg/m³ inhalable fraction, inhaled in the form of drops STEL: 0.2 mg/m³ inhaled droplets	TWA: 0.5 mg/m³ TWA: 0.2 mg/m³	TLV/LLV: 0.25 mg/m³ Sb total inhalable dust TLV/LLV: 0.1 mg/m³ Ni total dust		STEL: 1.5 mg/m³ TWA: 0.5 mg/m³ S*

Chemical name	European Union	Denmark	Finland	France
C.I. Pigment Brown 24				Total Chromium: 0.01

68186-90-3		mg/g creatinine in urine Total Chromium: 0.03
		ma/a creatinine in urine

## **Derived No Effect Level (DNEL)**

C.I. Pigment Yellow 53 (8007-18-9)

CATEGORY	Route of Exposure	Derived No Effect Level (DNEL)	UNITS
Chronic effects, systemic, workers	INHALATION	4	mg/m³

#### 8.2. Exposure controls

#### 8.2.1 Appropriate Engineering Controls

#### **Engineering controls**

Ensure adequate ventilation, especially in confined areas

Provide local exhaust ventilation

In case of insufficient ventilation, wear suitable respiratory equipment

Do not breathe dust

#### 8.2.2 Individual protection measures, such as personal protective equipment

## **Eye/Face Protection**

Wear safety glasses with side shields (or goggles)

#### **Skin and Body Protection**

Wear suitable protective clothing

Care should be taken in the selection of protective clothing to ensure that inflammation and irritation of the skin at neck and wrists through contact with the powder are avoided

## Hand protection

There is no one glove material or combination of materials that will give unlimited resistance to any individual or combination of chemicals

Ensure that the breakthrough time of the glove material is not exceeded. Refer to glove supplier for information on breakthrough time for specific gloves

The instructions and information provided by the glove manufacturer on use, storage, maintenance and replacement must be followed

Gloves should be replaced regularly and if there is any sign of damage to the glove material

Always ensure that gloves are free from defects and that they are stored and used correctly

The performance or effectiveness of the glove may be reduced by physical / chemical damage and poor maintenance Wear protective gloves

Break through time > 240 minutes Estimated

Glove thickness
> 0.56 mm
> 0.36 mm
> 0.51 mm
> 0.56 mm
> 0.48 mm
> 0.25 mm

## **Respiratory Protection**

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators

## **Thermal Protection**

No information available

## 8.2.3 Environmental exposure controls

Do not allow into any sewer, on the ground or into any body of water Local authorities should be advised if significant spillages cannot be contained

## Section 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1. Information on basic physical and chemical properties

Physical State Powder

Appearance No information available

**Odour** Odourless

ColourNo information availableOdour thresholdNo information availablePHNo information availableMelting point/freezing pointNo information available

Boiling point / boiling range No information available °C / °F

**Flash Point** 400 °C / 752 °F

Method

Evaporation Rate No information available Flammability (solid, gas) No information available

Flammability limit in air

Upper flammability limit:
Lower flammability limit
Vapour pressure
Vapour Density

No information available
No information available
No information available
No information available

Specific gravity 1.45

Solubility(ies) No information available **Partition coefficient** No information available **Autoignition Temperature** No information available **Decomposition temperature** No information available Kinematic viscosity No information available No information available Dynamic viscosity **Explosive Properties** No information available **Oxidising Properties** No information available

9.2. Other information

Molecular Weight No information available Minimum ignition energy (MIE) 3 - 50 mJ (typical range)

dust deflagration index (Kst) 100 - 199 bar\*m/s (typical range)

Minimum Explosive Conc. (g/m³) 20 - 70 (typical range)

## **Section 10: STABILITY AND REACTIVITY**

## 10.1. Reactivity

No information available

#### 10.2. Chemical stability

Stable under normal conditions

**Explosion Data** 

Sensitivity to Mechanical Impact No information available. Sensitivity to Static Discharge No information available.

#### 10.3. Possibility of hazardous reactions

Hazardous polymerisation None under normal processing

Possibility of hazardous reactions 
None under normal processing

#### 10.4. Conditions to avoid

Heat, flames and sparks

## 10.5. Incompatible materials

Strong oxidising agents

## 10.6. Hazardous decomposition products

Carbon monoxide

## Section 11: TOXICOLOGICAL INFORMATION

## 11.1. Information on toxicological effects

Information on Likely Routes of Exposure

**Eye Contact** 

No information available

Skin contact

No information available

**INGESTION** 

No information available

**INHALATION** 

No information available

## Numerical Measures of Toxicity - Product Information

The following values are calculated based on chapter 3.1 of the GHS document

**UNKNOWN ACUTE TOXICITY** 0% of the mixture consists of ingredient(s) of unknown toxicity.

## Numerical Measures of Toxicity - Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Propanedioic acid,	= 1500 mg/kg (Rat)		
[[3,5-bis(1,1-dimethylethyl)-4-hydrox			
yphenyl]methyl]butyl-,			
bis(1,2,2,6,6-pentamethyl-4-piperidi			
nyl) ester			

## Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin Corrosion/Irritation No information available Serious eye damage/eye irritation No information available Skin Sensitisation No information available **Respiratory Sensitisation** No information available **Germ Cell Mutagenicity** No information available Carcinogenicity No information available No information available Reproductive toxicity Specific target organ toxicity (single exposure) No information available Specific target organ toxicity (repeated exposure) No information available

Propanedioic acid, [[3,5-bis(1,1-dimethylethyl)-4-hydroxyphenyl]methyl]butyl-, bis(1,2,2,6,6-pentamethyl-4-piperidinyl)

ester

lymph system, Liver, Spleen

Aspiration Hazard Not applicable

## **Section 12: ECOLOGICAL INFORMATION**

## 12.1. Toxicity

Environmental Precautions Prevent product from entering drains

#### 12.2. Persistence and degradability

No information available.

## 12.3. Bioaccumulative potential

#### **Bioaccumulation**

No information available.

## 12.4. Mobility in soil

No information available.

#### 12.5. Results of PBT and vPvB assessment

No information available.

#### 12.6. Other adverse effects

No information available

## **Section 13: DISPOSAL CONSIDERATIONS**

#### 13.1. Waste treatment methods

**Environmental Precautions** Prevent product from entering drains

Keep out of waterways

Waste from Residues/Unused

**Products** 

Disposal should be in accordance with applicable regional, national and local laws and

regulations

Contaminated Packaging Improper disposal or reuse of this container may be dangerous and illegal

Empty containers must be scrapped or reconditioned

**European Waste Catalogue** 

**Product** 08 02 01 **Packaging** 15 01 10\*

## **Section 14: TRANSPORT INFORMATION**

IMDG RID ADR IATA ADN

14.1 UN/ID no NOT REGULATED NOT REGULATED NOT REGULATED NOT REGULATED NOT REGULATED

14.2 Proper Shipping

Name

14.3 Hazard class 14.4 Packing group

14.5 Environmental hazard

14.6 Special

Provisions

14.7 Transport in Bulk According to Annex II of MARPOL 73/78 and the IBC CODE

No information available

The supplier may apply one of the following exceptions: Combustible Liquid (49 CFR 173.150(f)); Consumer Commodity (49 CFR 173.150(c), ICAO/IATA SP A112); Limited Quantity (49 CFR 173.150(b), ICAO Part 3 Chapter 4, IATA 2.7, IMDG Chapter 3.4); Viscous Liquid (49 CFR 173.121(b), IMDG 2.3.2.2, IATA 3.3.3.1.1, ICAO 3.2.2, ADR 2.2.3.1.5); Does Not Sustain Combustion (49 CFR 173.120(a), IATA 3.3.1.3, ICAO 3.1.3, IMDG 2.3.1.3, ADR 2.2.3.1.1 Note 1); or others as allowed under hazardous materials/dangerous goods regulations.

## **Section 15: REGULATORY INFORMATION**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

## **European Union**

	Chemical name	EU - REACH (1907/2006) -	EU - REACH (1907/2006) -	EU - REACH (1907/2006) -
		Candidate List of Substances	Annex XIV - Substances Subject	Annex XVII - Restrictions on
L			to Authorization	Certain Dangerous Substances
Г	C.I. Pigment Yellow 53			Use restricted. See item 27.
	8007-18-9			

## **National Regulations**

ſ	Chemical name	French RG number	Title	Denmark - List of Undesirable Substances	Netherlands
Ī	C.I. Pigment Yellow 53	RG 37,RG 37bis			
	8007-18-9				

TA Luft (German Air Pollution Control Regulation)

Class 1 Class 2 Class 3 Class 4 0 % 7.5 % 0 %

31 . BlmSchV 0
Danish MAL Code 00 - 1

## 15.2. Chemical safety assessment

No information available

## **Section 16: OTHER INFORMATION**

#### **Supplier Address**

Sherwin-Williams UK Limited – General Industrial Division Goodlass Road Liverpool, Merseyside L24 9HJ +44 (0) 151 486 0486 Inver S.p.A. Via di Corticella, 205 Bologna, BO, Italy 40128 39 051 6380411 Inver Polska SP.Z.O.O. UL. Metalowców 49 Debica 39-200 Poland +48 14 680 90 20 Inver France S.A.S. 2 Rue Jean Devaux Boîte Postale 88 Thouars 79102 Phone: +33 5 49 96 025 00

Inver S.p.A. 10/A Via Marconi Minerbio BO 40061 Phone: +39 051 660 6811

#### Full text of H-Statements referred to under sections 2 and 3

H302 - Harmful if swallowed

H372 - Causes damage to organs through prolonged or repeated exposure

H410 - Very toxic to aquatic life with long lasting effects

Prepared by Product Stewardship

Revision Date 12-Sep-2022

**Revision note**No information available.

#### Disclaimer

The information on this Safety Data Sheet (SDS) is based on the present state of our knowledge, current national legislation and EU guidelines. As the specific conditions of use of the product are outside the supplier's knowledge and control the user is responsible for ensuring that the requirements of relevant legislation are complied with. This SDS should not be construed as any guarantee of the technical performance or suitability for particular applications. UNLESS SUPPLIER AGREES OTHERWISE IN WRITING, SUPPLIER MAKES NO WARRANTIES, EXPRESS OR IMPLIED, AND DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR USE OR FREEDOM FROM PATENT INFRINGEMENT. SUPPLIER WILL NOT BE LIABLE FOR ANY SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES.

## **End of Safety Data Sheet**