

# Mipa 2K-Klarlack-Spray inkl. Härter

## **Product Information**

Art.Nr.: 21291 0000 / 400 ml Art.Nr.: 21290 0000 / 250 ml

Mipa 2-Komponenten Klarlack-Spray is a fast drying, brilliant gloss clearcoat for the clear over base coating with an excellent flow. Highly resistant against all kinds of weathering, as well as chemical and mechanical strain. Fuel reistant!



#### Substrate:

Must be clean, free from oil, grease, and fat. Fully cured old paint



#### Pretreatment / Cleansing:

Pre-cleansing with Mipa Silikonentferner

### **Characteristics:**

High UV-protection, non-yellowing, lightfast High resistance against weathering Excellent flow and surface finish Safe and clean transfer of the hardener Very high resistance against chemical and mechanical strain Scratch and Fuel resistant!

D - 4/1218

Colour /

Colourless

**Grade of Gloss:** High gloss - mat on request!

Preparation:



Shake can vigorously until the mixing balls move freely!



Prior to coating, remove the red button from the safety cap, turn the spray can 180° and attach to the pin on the base of the aerosol.



Place the spray can upside down on a solid surface. Press red button with the ball of your hand until a stop is reached.

Shake can vigorously to mix the contents!

Application:



Spray to test - Spraying distance approx. 25 cm 2 - 3 coats, dry film thickness 40 - 50 µm.

Flash-off:



5 min. between each coating

After use:



Turn can upside down and spray until the valve is clean, this prevents the valve from clogging up.

**Drying Times:** 



Drying:

Dust dry 10 - 15 min. / 20°C Set to touch: 4 h / 20°C 24 h / 20°C

Fully cured: Polishing: 8 - 9 h / 20°C

Pot-Life: 5 - 6 h

**Processing** 

**Conditions:** From +10°C and up to 80% relative air humidity.

Storage: In tightly closed original containers at least 2 years shelf life

VOC-EC limiting value for the product (cat. B/e): 840 g/l Regulation: This product contains max. 840 g/l VOC [ 7.01 lbs/gal]

Safety

Information: Read the corresponding Material Safety Data Sheet