

PRODUCT DATASHEET

Molochite

PRODUCT INFORMATION

Coating type:

Inert china clay aggregate

Typical uses:

As a non-skid aggregate for use with the Dacrylate range of floor paints.

INSTRUCTIONS FOR USE

Method One:

Whilst the final coat of floor paint is still wet, sprinkle the Molochite evenly over the surface.

Spread rate for Molochite:

1-1½kg per 40m² depending on degree of 'non-skid' required.

Method Two:

Immediately prior to application of the final coat of floor paint, thoroughly mix into the paint, 1kg of Molochite.

The paint/Molochite mix should be stirred at intervals during application to prevent settling of Molochite additive.

Note.

The roughness or texture of the non-skid surface can be reduced if necessary by the application of a further thin-coat of the floor paint.

HEALTH AND SAFETY

Please refer to the following data sheets:

MOLO26 10761 Molochite

All work involving the application and use of this product should be performed in compliance with all relevant national, health, safety & environmental standards, and regulations

ADDITIONAL NOTES

The application and spray information given above is intended as a guide only. As conditions vary from job-to-job, it is the applicators responsibility to ensure all equipment in use has been set up to give the best results.

IMPORTANT INFORMATION

Datasheets are issued to supply general information on the product but without warranty. Since conditions of service and application are beyond our control we cannot accept claims for loss, damage, etc., based on this information. Dacrylate will not accept any claim for consequential or incidental damages.

© Dacrylate Paints Ltd. 2017

Lindley's Lane, Kirkby-in-Ashfield, Nottinghamshire NG17 8AL. Tel.: 01623 753845 Email: sales@dacrylate.co.uk

www.dacrylate.co.uk