

PRODUCT NAME

Coma Berenice

ORIGINALLY ISSUED

25/01/2017

PRODUCT CODE

TOPCOMA

VERSION

1.0

VERSION DATE

25/01/2017



PRODUCT DESCRIPTION

A super durable single pack marine varnish based on innovative polymer materials.

Coma Berenice offers outstanding physical properties including exceptional film build, ultra high gloss and excellent ultraviolet resistance.

Its ease of usage and high performance make it the first choice marine varnish for many boat owners.



IMPORTANT INSTRUCTIONS BEFORE USE

- Read and follow SDS, TDS and label instructions
- Stir all paints thoroughly before use
- Always use the same batch number on the same job
- Check colour & sheen. HMG will not accept any discrepancies arising after use
- Filter the product immediately before use
- Reduce emissions and maintain quality by replacing tin lid after use
- If in any doubt speak HMG Technical Service Department on (0161) 205 7631



SPECIAL PROPERTIES

- High Build.
- Excellent UV resistance.
- Ultra high gloss.



MAXIMUM VOC CONTENT (RFU)

0.44Kg/L



COLOUR RANGE

- Clear.



GENERAL INFORMATION

Coverage	10 square metres per litre
Flashpoint	31°C
Storage	Store between 5°C - 25°C. When not in use, cans must be kept sealed
Shelf Life	12 months from delivery date in original sealed containers



CLEANING

Surfaces must be clean, free from dust & totally dry.
Knotting solution may be used if appropriate.



SURFACE PREPARATION

Please refer to Knowledge Base on our website for details on Surface Preparation.



HEALTH AND SAFETY

- Refer to SDS and tin label prior to use.
- Contaminated Rags, Spray Booth Filters or other substrates should be segregated from other chemical waste, soaked with Water and disposed of in a non-combustible container with a tight fitting Lid.

APPLICATION METHODS



MIXING RATIO

COMPLIANT SPRAY GUN		BRUSH					
Base	1	Base	RFU				
Thinner	up to 10%						



HARDENER OPTIONS

--	--	--	--	--	--	--	--



THINNER OPTIONS

Thinner 2611							
--------------	--	--	--	--	--	--	--



VISCOSITY

		RFU					
--	--	-----	--	--	--	--	--



NUMBER OF COATS (GUIDE ONLY)

2-3 coats		2-3 coats					
-----------	--	-----------	--	--	--	--	--



DRYING TIME

Touch dry	5hrs@20°C	Touch dry	5hrs@20°C				
Hard dry	16-24hrs@20°C	Hard dry	16-24hrs@20°C				

**RECOATABILITY / OVERCOATING**

24hrs minimum

**WET FILM THICKNESS***

100 microns	100 microns		
-------------	-------------	--	--

**DRY FILM THICKNESS***

40 microns	40 microns		
------------	------------	--	--

* - HMG Technical Data Sheets indicate a Dry Film Thickness that will be achieved when applying a particular Wet Film Thickness. These values are a guide only and are not to be used as specifications. Film thickness will vary depending on actual use and specification. Great care should be taken to achieve the dft stated in the agreed specification and to avoid areas of excessively low or high thickness.

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is to the best of HMG's knowledge and belief accurate and reliable as of the date indicated. However, no representation, warranty or guarantee is made as to it's accuracy, reliability or completeness. It is the user's responsibility to satisfy themselves as to the suitability and completeness of such information for their own particular use. For professional use only.