



SAFETY DATA SHEET THINNERS R70

According to Regulation (EC) No 1907/2006, Annex II, as amended by Regulation (EU) No 453/2010, According to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the	ne substance/mixture and of the company/undertaking	
1.1. Product identifier		
Product name	THINNERS R70	
Product number	0500-TR70	
1.2. Relevant identified uses o	f the substance or mixture and uses advised against	
Identified uses	Solvent/Thinner	
1.3. Details of the supplier of the	he safety data sheet	
Supplier	Dacrylate Paints Ltd, Lime Street, Kirkby-in-Ashfield Nottingham NG17 8AL Tel: +44 (0) 1623-753845 Fax: +44 (0) 1623-757151	
Contact person	sales@dacrylate.co.uk	
1.4. Emergency telephone nur	nber	
National emergency telephone +44 (0) 1623 753845 08:30-17:00 MON-FRI number		
SECTION 2: Hazards identification	ation	
SECTION 2: Hazards identification of the substant		
2.1. Classification of the subst	ance or mixture	
2.1. Classification of the subst <u>Classification</u> Physical hazards	ance or mixture Flam. Liq. 3 - H226	
2.1. Classification of the subst <u>Classification</u> Physical hazards Health hazards	ance or mixture Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304	
2.1. Classification of the subst <u>Classification</u> Physical hazards	ance or mixture Flam. Liq. 3 - H226	
2.1. Classification of the subst <u>Classification</u> Physical hazards Health hazards	ance or mixture Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
2.1. Classification of the subst <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or	ance or mixture Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411	
2.1. Classification of the subst <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or 1999/45/EC)	Ance or mixture Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 Xn;R65. N;R51/53. R10. Prolonged and repeated contact with solvents over a long period of time may lead to	
2.1. Classification of the subst <u>Classification</u> Physical hazards Health hazards Environmental hazards Classification (67/548/EEC or 1999/45/EC) Human health	ance or mixture Flam. Liq. 3 - H226 STOT RE 1 - H372 Asp. Tox. 1 - H304 Aquatic Chronic 2 - H411 Xn;R65. N;R51/53. R10. Prolonged and repeated contact with solvents over a long period of time may lead to permanent health problems. The majority of solvents are volatile. Provide adequate ventilation to reduce build up of solvent	

Pictogram
1 lologiani



Signal word	Danger
Hazard statements	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.
Precautionary statements	 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapour/spray. P280 Wear protective gloves/protective clothing/eye protection/face protection. P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor. P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. P314 Get medical advice/attention if you feel unwell. P370+P378 In case of fire: Use foam, carbon dioxide, dry powder or water fog to extinguish. P403+P235 Store in a well-ventilated place. Keep cool. P501 Dispose of contents/container in accordance with national regulations.
Contains	ALIPHATIC H/C (138/162)
Supplementary precautionary statements	 P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P264 Wash contaminated skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P273 Avoid release to the environment. P331 Do NOT induce vomiting. P391 Collect spillage. P405 Store locked up.

2.3. Other hazards

This product does not contain any substances classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

ALIPHATIC H/C (138/162)		60-100%
CAS number: 64742-88-7		
Classification	Classification (67/548/EEC or 1999/45/EC)	
Flam. Liq. 3 - H226	Xn;R65. N;R51/53. R10.	
STOT RE 1 - H372		
Asp. Tox. 1 - H304		
Aquatic Chronic 2 - H411		

4.1. Description of first aid measures

General information	The severity of the symptoms described will vary depending on the concentration and the length of exposure. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.
Inhalation	Get medical attention. Place unconscious person on their side in the recovery position and ensure breathing can take place. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Get medical attention. Symptoms of lung oedema (shortness of breath) may develop up to 24 hours after exposure. Show this Safety Data Sheet to the medical personnel.
Ingestion	Remove affected person from source of contamination. Rinse mouth thoroughly with water. Give plenty of water to drink. DO NOT induce vomiting. Get medical attention immediately.
Skin contact	Wash skin thoroughly with soap and water. Get medical attention promptly if symptoms occur after washing. Use barrier creams to prevent skin contact. Remove contaminated clothing and rinse skin thoroughly with water.
Eye contact	Rinse immediately with plenty of water. Remove any contact lenses and open eyelids wide apart. Continue to rinse for at least 15 minutes. Get medical attention if irritation persists after washing. Show this Safety Data Sheet to the medical personnel.
Protection of first aiders	First aid personnel should wear appropriate protective equipment during any rescue. In case of insufficient ventilation, wear suitable respiratory equipment.
4.2. Most important symptoms	and effects, both acute and delayed
General information	The severity of the symptoms described will vary dependent on the concentration and the length of exposure.
Inhalation	Harmful if inhaled Vapours may cause headache, fatigue, dizziness and nausea.
Ingestion	Harmful if swallowed. May cause nausea, stomach paint and vomiting.
Skin contact	Skin irritation. May cause sensitisation or allergic reactions in sensitive individuals.
Eye contact	May cause severe eye irritation.
4.3. Indication of any immedia	te medical attention and special treatment needed
Notes for the doctor	No specific recommendations. If in doubt, get medical attention promptly. In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
SECTION 5: Firefighting meas	sures
5.1. Extinguishing media	
Suitable extinguishing media	Use fire-extinguishing media suitable for the surrounding fire. Extinguish with foam, carbon dioxide or dry powder.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising fr	om the substance or mixture
Specific hazards	Vapours are heavier than air and may travel along the floor and accumulate in the bottom of containers. Vapours may be ignited by a spark, a hot surface or an ember. Vapours may form explosive mixtures with air. If a fire or if heated, a pressure increase will occur and the container may burst with the risk of subsequent explosion. The product is flammable.

Hazardous combustion products	In case of fire, toxic gases (CO, CO2, NOx) may be formed. Acrid smoke or fumes. Other pyrolysis products typical of burning an organic material. In case of fire, toxic gases (CO, CO2, NOx) may be formed. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. In the event of a fire and/or explosion, do not breathe fumes.
5.3. Advice for firefighters	
Protective actions during firefighting	Containers close to fire should be removed or cooled with water. Do not allow water to contact any leaked material. Keep up-wind to avoid fumes. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities. Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken without appropriate training or involving any personal risk.
Special protective equipment for firefighters	Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing.
SECTION 6: Accidental release	e measures
6.1. Personal precautions, prot	tective equipment and emergency procedures
Personal precautions	Do not handle broken packages without protective equipment. Provide adequate ventilation. If ventilation is inadequate, suitable respiratory protection must be worn. Wash thoroughly after dealing with a spillage. No smoking, sparks, flames or other sources of ignition near spillage.
For non-emergency personnel	Do not touch or walk through spilt material. Avoid breathing vapour or mist. Provide adequate ventilation. Wear suitable respirator when ventilation is inadequate. Put on appropriate personal protective equipment. No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering.
For emergency responders	If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable materials. See also the information in "For non-emergency personnel".
6.2. Environmental precautions	S
Environmental precautions	Do not discharge into drains or watercourses or onto the ground.
6.3. Methods and material for o	containment and cleaning up
Methods for cleaning up	No smoking, sparks, flames or other sources of ignition near spillage. Collect and place in suitable waste disposal containers and seal securely. Label the containers containing waste and contaminated materials and remove from the area as soon as possible. If involved in a fire, shut off flow if it can be done without risk. Eliminate all sources of ignition. No smoking, sparks, flames or other sources of ignition near spillage. Provide adequate ventilation. Small Spillages: Absorb small quantities with paper towels and evaporate in a safe place. Large Spillages: Absorb in vermiculite, dry sand or earth and place into containers. The accumulation of contaminated rags and application cloths may result in spontaneous combustion. This is particularly important in the case of products containing a high level of drying oils such as teak oil, linseed oil etc. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.
6.4. Reference to other section	IS
Reference to other sections	Wear protective clothing as described in Section 8 of this safety data sheet. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see section 13.
SECTION 7: Handling and stor	rage

7.1. Precautions for safe handling

Usage precautions	Avoid contact with skin and eyes. Eliminate all sources of ignition. Keep away from heat, sparks and open flame. All handling should only take place in well-ventilated areas. Dust may form explosive mixture with air. Take precautionary measures against static discharges. Storage tanks and other containers must be earthed. Persons with a history of skin sensitization problems should not be employed in any process in which this product is used.
Advice on general occupational hygiene	Do not eat, drink or smoke when using this product. Wash promptly with soap and water if skin becomes contaminated. Promptly remove any clothing that becomes contaminated. Use appropriate hand lotion to prevent defatting and cracking of skin.
7.2. Conditions for safe storage	e, including any incompatibilities
Storage precautions	Keep away from oxidising materials, heat and flames. Keep container tightly closed and in a well-ventilated place. Avoid/separate from strong acids, alkalis, oxidising and reducing agents. Observe the label precautions. Containers which have been opened must be carefully resealed and kept upright to prevent leakage.
Storage class	Flammable liquid storage.
7.3. Specific end use(s)	
Specific end use(s)	The identified uses for this product are detailed in Section 1.2. Restricted to professional users.
SECTION 8: Exposure Controls/personal protection	
8.1. Control parameters	
Ingredient comments	WEL = Workplace Exposure Limits

8.2. Exposure controls

Protective equipment

ſſŊ

Note:	When spraying, the use of a suitable/approved respirator is advised.
Appropriate engineering controls	No specific ventilation requirements noted, but forced ventilation may still be required if air contamination exceeds acceptable level.
Eye/face protection	The following protection should be worn: Chemical splash goggles. Eyewear complying with an approved standard should be worn if a risk assessment indicates eye contact is possible.
Hand protection	Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material. To protect hands from chemicals, gloves should comply with European Standard EN374.
Other skin and body protection	Wear appropriate clothing to prevent skin contamination. Use barrier creams to prevent skin contact.
Hygiene measures	Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station. Provide eyewash station and safety shower. Wash hands at the end of each work shift and before eating, smoking and using the toilet. Wash promptly if skin becomes contaminated.

Respiratory protection	If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Ensure all respiratory protective equipment is suitable for its intended use and is 'CE'-marked.
Environmental exposure controls	Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels. Keep container tightly sealed when not in use.

SECTION 9: Physical and Chemical Properties

3.1. Information on basic physi	ical and chemical properties
Appearance	Liquid.
Colour	Colourless.
Odour	Characteristic/of solvents
Odour threshold	Not determined.
рН	Not relevant.
Melting point	Not determined.
Initial boiling point and range	Not determined.
Flash point	~ 25°C CC (Closed cup).
Evaporation rate	Not determined.
Evaporation factor	Not determined.
Flammability (solid, gas)	No specific test data are available.
Upper/lower flammability or explosive limits	Lower flammable/explosive limit: 0.8% Upper flammable/explosive limit: 6%
Other flammability	Not known.
Vapour pressure	Not determined.
Vapour density	Not determined.
Relative density	~ 0.76 @ @ 20°C
Bulk density	Not determined.
Solubility(ies)	Soluble in the following materials: Organic solvents.
Partition coefficient	Not available.
Auto-ignition temperature	Not determined.
Decomposition Temperature	Not determined.
Viscosity	Not determined.
Explosive properties	May form explosive mixtures with air.
Explosive under the influence of a flame	Not considered to be explosive.
Oxidising properties	Not determined.
Comments	Information given is applicable to the product as supplied.

9.1. Information on basic physical and chemical properties

9.2. Other information Other information None. SECTION 10: Stability and reactivity 10.1. Reactivity Reactivity The following materials may react with the product: Acids. Alkalis. Oxidising materials. 10.2. Chemical stability Stability Stable at normal ambient temperatures and when used as recommended. Further information on correct storage: refer to Section 7. 10.3. Possibility of hazardous reactions Possibility of hazardous None under normal processing Vapours may form explosive mixtures with air. reactions 10.4. Conditions to avoid Conditions to avoid Avoid contact with strong oxidising agents. Do not pressurise, cut, weld, braze, solder, drill, grind or expose containers to conditions to heat or sources of ignition. Protection against nuisance dust must be used when the airborne concentration exceeds 10 mg/m3. Avoid extremes of temperature and direct sunlight. 10.5. Incompatible materials Materials to avoid Strong oxidising agents. 10.6. Hazardous decomposition products Hazardous decomposition Thermal decomposition or combustion products may include the following substances: products Carbon monoxide (CO). Carbon dioxide (CO2). Oxides of nitrogen. Acrid smoke or fumes. In case of fire and/or explosion, do not breaths fumes. **SECTION 11: Toxicological information**

11.1. Information on toxicological effects

General information	This product is unlikely to harm health, given normal and proper handling and hygienic precautions. Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	Harmful by inhalation. Irritating to respiratory system.
Ingestion	Irritating. May cause nausea, stomach pain and vomiting.
Skin contact	Harmful in contact with skin. Irritating to skin.
Eye contact	Harmful in contact with eyes. Irritating to eyes.
Acute and chronic health hazards	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems. Prolonged or repeated exposure to vapours in high concentrations may cause the following adverse effects: Nausea, vomiting. Headache. Gas or vapour may irritate the respiratory system. Product has a defatting effect on skin. Acts as a defatting agent on skin. May cause cracking of skin, and eczema. May cause allergy.
Route of entry	Inhalation Ingestion. Skin and/or eye contact Oral
Additional Information:	For further information, please refer to Sections 4 and 8 respectively
T	

Toxicological information on ingredients.

ALIPHATIC H/C (138/162)

Toxicological effects	Prolonged or repeated contact can defat the skin and lead to irritation, cracking and/or dermatitis. High vapour concentrations can cause headaches, dizziness and nausea.
Acute toxicity - oral	
Acute toxicity oral (LD₅₀ mg/kg)	5,051.0
Species	Rat
ATE oral (mg/kg)	5,051.0
Acute toxicity - dermal	
Acute toxicity dermal (LD₅₀ mg/kg)	4,001.0
Species	Rabbit
ATE dermal (mg/kg)	4,001.0
Serious eye damage/irritati	ion
Serious eye damage/irritation	Not Irritating
Respiratory sensitisation	
Respiratory sensitisation	There is no evidence that the product can cause respiratory hypersensitivity.
Skin sensitisation	
Skin sensitisation	Not expected to be a skin sensitizer
Germ cell mutagenicity	
Genotoxicity - in vitro	Negative.
Genotoxicity - in vivo	Negative.
Carcinogenicity	
Carcinogenicity	No evidence of carcinogenicity Not classified carcinogenic
Reproductive toxicity	
Reproductive toxicity - fertility	NOAEC > 300 Inhalation. Rat Units ppm
Reproductive toxicity - development	- : NOAEC > 300 Inhalation. Rat Units ppm , ,
Specific target organ toxicit	ty - single exposure
STOT - single exposure	No information available.
Target organs	Central nervous system
Specific target organ toxicit	ty - repeated exposure
STOT - repeated exposure	NOAEL > 1000 mg/lt (Oral Rat)

Target organs	Central nervous system
Aspiration hazard	
Aspiration hazard	No information available.
General information	Prolonged and repeated contact with solvents over a long period may lead to permanent health problems.
Inhalation	No specific health hazards known.
Ingestion	May be harmful if swallowed. May cause stomach pain or vomiting.
Skin contact	Acts as a defatting agent on skin. May cause cracking of skin, and eczema.
Eye contact	No specific health hazards known. May cause eye and respiratory system irritation.
Route of entry	Skin and/or eye contact Inhalation
Target organs	Central nervous system
12: Ecological Information	

SECTION 12: Ecological Information

Ecotoxicity

Large quantities of the product should not be allowed to enter drains or water courses or be deposited where it can affect ground or surface waters.

12.1. Toxicity

Ecological information on ingredients.

ALIPHATIC H/C (138/162)

Toxicity		This product contains substances which are harmful to aquatic organisms. Do not discharge into drains, water courses or onto the ground.
Acute toxicity - fi	sh	, LC50 96 hours < 300 mg/lt:,
Acute toxicity - a invertebrates	quatic	, NOEC 21 Days 0.097 mg/lt (Daphnia magna):,
Acute toxicity - a plants	quatic	No information available.
Acute toxicity - microorganisms		, EC50 48 hours 43.98 mg/lt: ,
Acute toxicity - te	errestrial	No information available.
12.2. Persistence and degrada	ability	
Persistence and degradability	There a	re no data on the degradability of this product.
Biodegradation	Not dete	ermined.

Ecological information on ingredients.

ALIPHATIC H/C (138/162)

Persistence and degradability

The product is readily biodegradable.

Biodegradation	Degradation (%)
40.0 Discoursulative retent	75% (28 days)
12.3. Bioaccumulative potent	
Bioaccumulative potential	The product contains potentially bioaccumulating substances.
Partition coefficient	Not available.
Ecological information on ing	
	ALIPHATIC H/C (138/162)
Bioaccumulative	e potential No data available on bioaccumulation.
12.4. Mobility in soil	
Mobility	The product is insoluble in water and will spread on the water surface.
Ecological information on ing	redients.
	ALIPHATIC H/C (138/162)
Mobility	No information available. The product contains volatile organic compounds (VOCs) which will evaporate easily from all surfaces.
12.5. Results of PBT and vPv	/B assessment
Results of PBT and vPvB assessment	This product does not contain any substances classified as PBT or vPvB.
Ecological information on ing	redients.
	ALIPHATIC H/C (138/162)
Results of PBT assessment	and vPvB This product does not contain any substances classified as PBT or vPvB.
12.6. Other adverse effects	
Other adverse effects	Not known.
SECTION 13: Disposal consi	derations
13.1. Waste treatment metho	ds
General information	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. This material and its container must be disposed of in a safe way. The generation of waste should be minimised or avoided wherever possible. The company encourages the recycle, recovery and reuse of materials, wherever possible.
Disposal methods	Dispose of waste to licensed waste disposal site in accordance with the requirements of the local Waste Disposal Authority. Avoid the spillage or runoff entering drains, sewers or watercourses. Residues and empty containers should be taken care of as hazardous waste according to local and national provisions. Dispose of waste via a licensed waste disposal contractor. Dispose of contents/container in accordance with national regulations.
SECTION 14: Transport infor	mation
General	To avoid the risk of spillage, always store and transport in a secure, upright position. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

14.1. UN number

1263
1263
1263
1263
)
PAINT
PAINT
PAINT
PAINT
s)
3
F1
3
3
3
3

Transport labels



14.4. Packing group	
ADR/RID packing group	Ш
IMDG packing group	Ш
ADN packing group	Ш
ICAO packing group	Ш

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant No.

14.6. Special precautions for	user
-------------------------------	------

F-E, S-E
3
•3YE
33
(D/E)

14.7. Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code

Transport in bulk according to Not applicable. Annex II of MARPOL 73/78 and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture	
National regulations	Petroleum (Consolidation) Act, as amended 1984 SI 1244. Highly Flammable Liquid Regulations 1972.
	Rivers (Prevention of Pollution) Act 1961.
	Control of Pollution (Special Waste) Regulations 1980 (as amended).
	Control of Substances Hazardous to Health Regulations 2002 (as amended).
EU legislation	Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18
	December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH) (as amended).
	Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16
	December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
	Commission Directive 2000/39/EC of 8 June 2000 establishing a first list of indicative
	occupational exposure limit values in implementation of Council Directive 98/24/EC on the protection of the health and safety of workers from the risks related to chemical agents at work (as amended).
	Commission Regulation (EU) No 453/2010 of 20 May 2010.
Guidance	Workplace Exposure Limits EH40.
	Introduction to Local Exhaust Ventilation HS(G)37.
	CHIP for everyone HSG228.
	Approved Classification and Labelling Guide (Sixth edition) L131.
	Safety Data Sheets for Substances and Preparations.

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information	
General information	Product to be used in industrial and/or professional applications.
Issued by	BOD
Revision date	20/03/2015
Revision	0
SDS number	10183
Risk phrases in full	R10 Flammable. R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. R65 Harmful: may cause lung damage if swallowed.
Hazard statements in full	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H372 Causes damage to organs through prolonged or repeated exposure. H411 Toxic to aquatic life with long lasting effects.

The product should not be used for the purposes other than those shown in Section 1 without first referring to the supplier and obtaining written handling instructions. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant legislation are complied with. This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.